

MALIBU

WAVESCAPE

Modern Subway

12x24, 2x2 Mosaic, 3x8 Brick Mosaic


TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.



VENICE

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9mm

| Characteristics: | Norms: | Results |
|---------------------------------|-----------|------------|
| Water Absorption | ASTM C373 | ≤ 0.5 % |
| Breaking Strength | ASTM C648 | ≥ 400 lbs |
| Dynamic Coefficient of Friction | AcuTest | ≥ 0.42 |
| Thickness Dimension | ASTM C499 | Complies |
| Facial Dimension | ASTM C499 | Complies |
| Warpage Diagonal | ASTM C485 | Complies |
| Wedging | ASTM C502 | Complies |
| Chemical Resistance | ASTM C650 | Unaffected |
| Scratch Hardness | MOHS | 6 |

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com