

COCONUT



RAIN



SEASHELL



SEPIA



CERULEAN



PETROLEUM



NAVY



AQUAMARINE



EUCALYPTUS



PINK PROSECCO



WELLFLEET

Handmade Look
2x6.5, 5x5, .5x13 Liner


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 1 Rated for wall application only

PERFORMANCE DATA

THICKNESS: 8.6 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	10 %
Abrasion Resistance (Glazed)	ISO 10545-7	1/5
Chemical Resistance	ISO 10545-13	Conforms
Resistance to Stains	ISO 10545-14	Conforms
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com